

- prestatieverklaring -

LOOD

Voor ons lood werken wij samen met twee verschillende producenten.
Afhankelijk van de beschikbaarheid op het moment gebruiken wij het lood van de ene of van de andere producent. De kwaliteit is echter van beide producenten gelijkwaardig, wat ook af te leiden valt uit de volgende DOP's.



British Lead

Declaration of Performance

DECLARATION OF PERFORMANCE
2013-07-01



1. Unique identification code of the product type:

Rolled Lead Sheet to BSEN 12588: 2006

2. Type, batch or serial number or any other element allowing identification of the construction product as required under **Article 11 (4) of the CPR**:

Products are colour coded to denote their thickness (see item 8). Packaging will illustrate other production data.

3. Intended use or uses of the construction product in accordance with the application harmonised technical specification, as foreseen by the manufacturer:

Rolled Lead Sheet for Construction, Nuclear and Engineering.

4. Name, registration trade name or registered trade mark and contact address of the manufacturer as required under **Article 11 (5)**.

**British Lead
Peartree Lane
Welwyn Garden City
Hertfordshire
AL7 3UB**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in **Article 12 (2)**.

**Jon Lemon
British Lead
Peartree Lane
Welwyn Garden City
Hertfordshire
AL7 3UB**

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in **CPR, Annex V**:

System 4

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

EN 14783: 2006 (see also BS EN 12588 2006)



Essential Characteristics	Performance	Harmonised Technical Specification															
Appearance	Bluish grey soft metal	EN 14783:2006															
Melting Temperature	327°c																
Fuming Temperature	500°c																
Boiling Point	1,750°c																
Density	11,34g/cm3																
Fire Rating	A1 & A1FL																
Odour	No Performance Detected (NPD)																
Flash Point	No Performance Detected (NPD)																
Solubility in Water	Insoluble																
Chemical Composition	% by mass (m/m)																
Copper	0.03 to 0.06																
Antimony	max 0.005																
Bismuth	max 0.100																
Silver	max 0.005																
Tin	max 0.05																
Zinc	max 0.001																
Other impurities	max 0.005																
Lead	Remainder																
<table border="1"> <thead> <tr> <th>Nominal Thickness (mm)</th> <th>Colour</th> </tr> </thead> <tbody> <tr> <td>1.25 or 1.32</td> <td>green</td> </tr> <tr> <td>1.50 or 1.59</td> <td>yellow</td> </tr> <tr> <td>1.75 or 1.80</td> <td>blue</td> </tr> <tr> <td>2.00 or 2.24</td> <td>red</td> </tr> <tr> <td>2.50 or 2.65</td> <td>black</td> </tr> <tr> <td>3.00 or 3.15</td> <td>white</td> </tr> <tr> <td>3.50 or 3.55</td> <td>orange</td> </tr> </tbody> </table>	Nominal Thickness (mm)	Colour	1.25 or 1.32	green	1.50 or 1.59	yellow	1.75 or 1.80	blue	2.00 or 2.24	red	2.50 or 2.65	black	3.00 or 3.15	white	3.50 or 3.55	orange	Max deviation from the ordered nominal thickness, when measured shall be carried out on flat undamaged areas, at each end of the roll or split roll, at least 20mm away from the edge to avoid any burrs, physical marks and creases shall not exceed $\pm 5\%$.
Nominal Thickness (mm)	Colour																
1.25 or 1.32	green																
1.50 or 1.59	yellow																
1.75 or 1.80	blue																
2.00 or 2.24	red																
2.50 or 2.65	black																
3.00 or 3.15	white																
3.50 or 3.55	orange																
Width	The maximum deviation from the ordered nominal width shall not exceed $\pm 5\text{mm}$.																
Length	The maximum deviation from the ordered nominal length shall not exceed $+50\text{mm}$.																



9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in points 8. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Joss Campbell, MANAGING DIRECTOR

(Name and function)

Widway Garden City 18th June 2013

(place and date of issue)

(signature)

→ **Le Plomb Français SARL**

Z.I. Le Bois Chevalier
60190 Estrées-St-Denis
France

Tél. +33 (0)344 413131
Fax +33 (0)344 410090

Administration

Tél. +33 (0)344 410118

contact@leplombfrancais.fr
www.leplombfrancais.fr

Declaration of Performance

DECLARATION OF PERFORMANCE

No **1300017Z** CPR **2013-07-01**

1. Unique identification code of the product type:

Rolled Lead Sheet to EN 12588: 2006

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11 (4) of the CPR:

Products are colour coded to denote their thickness (see item 8). Packaging will illustrate other production data.

3. Intended use or uses of the construction product in accordance with the application harmonised technical specification, as foreseen by the manufacturer:

Rolled Lead Sheet for Construction, Nuclear and Engineering.

4. Name, registration trade name or registered trade mark and contact address of the manufacturer as required under Article 11 (5).

Le Plomb Français
52 rue de Compiègne
60190 Estrées Saint Denis
France

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2).

Not concerned

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

System 4

7. In case of the declaration of performance concerning a construction product covered by a harmonized standard:

EN 14783: 2006 (see also EN 12588 2006)

8. Declared Performance

Essential Characteristics	Performance	Harmonised Technical Specification
Appearance	Bluish grey soft metal	EN 14783:2006
Melting Temperature	327°c	
Fuming Temperature	500°c	
Boiling Point	1,750°c	
Density	11,34g/cm3	
Fire Rating	A1 & A1FL	
External Fire Performance	FROFF(t1), FROFF(t2) & FROFF(t3)	
Odour	No Performance Detected (NPD)	
Flash Point	No Performance Detected (NPD)	
Solubility in Water	Insoluble	
Chemical Composition	% by mass (m/m)	
Copper	0.03 to 0.06	
Antimony	max 0.005	
Bismuth	max 0.100	
Silver	max 0.005	
Tin	max 0.05	
Zinc	max 0.001	
Other impurities	max 0.005	
Lead	Remainder	
Nominal Thickness (mm) & Colour Code	Max deviation from the ordered nominal thickness, when measured shall be carried out on flat undamaged areas, at each end of the roll or split roll, at least 20mm away from the edge to avoid any burrs, physical marks and creases shall not exceed $\pm 5\%$.	
1.25 or 1.32 : Green		
1.50 or 1.59 : Yellow		
1.75 or 1.80 : Blue		
2.00 or 2.24 : Red		
2,50 or 2.65 : Black		
3.00 or 3.15 : White		
3.50 or 3.55 : Orange		
Width	The maximum deviation from the ordered nominal width shall not exceed $\pm 5\text{mm}$.	
Length	The maximum deviation from the ordered nominal length shall not exceed +50mm.	

9. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

François LECLERCQ, Managing Director

Estrées Saint Denis le 17 juin 2013

